



ICRC/IFRC STANDARD

CUSTOMER REFERENCE

HSHEBLANPMT1

05787

DESCRIPTION

- » Knitted blanket dry raised on both sides
- » 2 fold fleece layers in 100% virgin polyester
- » Min. 400 gsm - max. 700 gsm

MAIN MATERIALS

MATERIAL	100% virgin polyester on dry weight as per ISO 1833
TENSILE STRENGTH	Min. 250 N warp and weft as per ISO 13934-1
TENSILE STRENGTH LOSS	Less than 5% after washing as per ISO 6330 & ISO 13934-1
THICKNESS	Min 6,5mm as per ISO 5084 (1KPA on 2000 mm ²)
SHRINKAGE	Less than 5% after washing as per ISO 6330
WEIGHT LOSS	Less than 5% after washing as per ISO 6330
TOG	Min. 2,5 RCT (= 2,5 TOG)
RESISTANCE TO AIRFLOW	Less than 1000 L/m ² /s as per ISO 9237 under 100 Pa pressure drop
FINISH	Seam of 10 to 13 stitches per 10 cm
ORGANOLEPTIC TEST	No bad smell, not irritating, no dust, PH between 4 and 9, fit for human use and free from harmful VOC
FLAME RESISTANCE	Flame proof as per ISO 12952-2
CIGARETTE RESISTANCE	Cigarette proof as per ISO 12952-1
COLOR	Grey shade blanket

DIMENSIONS

LENGTH x WIDTH	150 x 200 cm ± 1%
WEIGHT	Min. 400 g - max. 700 gsm

PACKING

PACKING UNIT (P.U.)	Bale
QTY P.U.	15 pcs per bale
P.U. MEASUREMENTS	DIMENSIONS: 80 x 50 x 50 cm WEIGHT: 20 kg VOLUME: 0,2 m ³
QTY PALLET	4 to 8 bales per CRI pallet
PALLET MEASUREMENTS	DIMENSIONS: 115 x 75 x 195 cm WEIGHT: 168 kg VOLUME: 1,68 m ³
LOADING	PER 20 FT DC 2100 pcs unpalletized 1800 pcs palletized PER 40 FT DC 4200 pcs unpalletized 3600 pcs palletized PER 40 FT HC 5400 pcs unpalletized 3600 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.
FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

Specifications & design may be altered without notice due to continuous product development.
LAST UPDATED 6/2023