

BASE TENT 33,6 SQM



FUNGI / MOLD
RESISTANT



UV RESISTANT



ALL CLIMATES



EASY SETUP



MSF/ICRC/IFRC STANDARD MULTIPURPOSE TENT

DESCRIPTION

- » Multipurpose tent, can be used for storage, hospital, dispensary, school, office, ...
- » Tents can be connected one to another to make a longer structure
- » Various options available (inner tent, partitions sets,...)

MAIN MATERIALS

OUTER TENT LINER	Roof: 440 gsm polyester cotton - water, rot and UV proof Wall: 320 gsm polyester cotton - water, rot and UV proof
MUD FLAP	550 gsm polyester with PVC coating on both sides - water, rot and UV proof
GROUND SHEET (OPTIONAL)	550 gsm polyester with PVC coating on both sides - water, rot and UV proof
FRAME	Aluminium pipe Ø 42 x 2 mm with steel cross pieces Galvanized steel pipe Ø 30 x 1,5 mm

DIMENSIONS

LENGTH x WIDTH OUTER TENT	600 x 560 cm
FLOOR SURFACE	33,6 sqm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	211 cm

BASE TENT 33,6 SQM

PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 3 years
LIFE SPAN	Min. 12 months exposure in all climates, with proper anchoring and maintenance
TREATMENT	Fungi/mould resistant treated
SETUP	Easy setup (20 min 3 persons)
COLOR	Tent liner: natural white Groundsheet: grey

PACKING

PACKING UNIT (P.U.)	PVC bag
CONTENT P.U.	Tent, frame, accessories and hammer
QTY P.U.	1 piece
P.U. MEASUREMENTS	DIMENSIONS: 225 x 45 x 43 cm WEIGHT: 130 kg VOLUME: 0,435 m ³
QTY PALLET	4 pcs
PALLET MEASUREMENTS	DIMENSIONS: 225 x 95 x 112 cm WEIGHT: 545 kg VOLUME: 2,405 m ³
LOADING	PER 20 FT DC 48 pcs palletized PER 40 FT DC 96 pcs palletized PER 40 FT HC 96 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.
FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

ADD-ONS

Connectability options (gable / lateral / cross connector)
Groundsheet
Partition set
Ceiling net
Shade net
Inner liner