
# PLASTIC SHEETING 4 X 60 M

### **PLASTIC SHEETING**









FLAME RETARDANT EN 13823+A1







ICRC/IFRC STANDARD

**CUSTOMER REFERENCE** 

HSHETARPW460

## **DESCRIPTION**

# » Reinforced flexible tarpaulins for temporary shelter or protection

» Made of woven HDPE black fibres

#### **DIMENSIONS**

LENGTH x WIDTH  $4 \times 60 \text{ m}$ WEIGHT  $190 \text{ g/m}^2$ 

 $190 \text{ g/m}^2 \pm 20 \text{ g}$ , plus 10% for the reinforcement bands (approx. 5 kg)

#### **MAIN MATERIALS**

MATERIAL Woven HDPE black fibers fabric laminated on both sides with LDPE coating with 6 reinforced bands

made of HDPE in the length I Prepunched 8 mm holes on the 2 side bands at 0,1 m intervals

UV RESISTANCE Max. 20% loss on original tensile strength and not less than 475N after

1500 UV exposure (UVB 313nm peak)

TEMPERATURE RESISTANCE -20 to 80°C

TENSILE STRENGTH Min. 500 N and 15% to 25% elongation in warp and weft as per ISO 1421-1

Min. 700 N inside the reinforcement bands as per ISO 1421-1

TEARING STRENGTH Min. 100 N as per ISO 4674-1B

COLOR White with dark grey reinforcement bands I Inner black fibres to ensure opacity

LOGO PRINTING Upon customer request

#### **PACKING**

PACKING UNIT Roll
PACKED QTY PER PACKING UNIT 1 pcs

DIMENSIONS I WEIGHT I VOLUME  $210 \times 20 \times 20 \text{ cm}$  I 45 kg I  $0,084 \text{ m}^3$ 

PACKED QTY PER PALLET 18 to 20 pcs per metal stackable pallet

DIMENSIONS I WEIGHT I VOLUME 225 x 105 x 112 cm | 880 to 910 kg | 2,646 m³

PACKED QTY PER 20 FT DC 210 pcs unpalletized I 186 pcs palletized

PACKED QTY PER 40 FT DC 530 pcs unpalletized I 408 pcs palletized

PACKED QTY PER 40 FT HC 530 pcs unpalletized I 408 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION

#### **STOCKS**

Belgium, China

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 10/2021