

XPERT TENT 72 SQM



FLAME RETARDANT
CPAI-84 / 6



GOOD WIND
RESISTANCE



UV RESISTANT



DISINFECTABLE



EASY SETUP



ALL CLIMATES



DESCRIPTION

- » New generation of multipurpose tents
- » Removable groundsheet included.
- » Integrated / removable shade cover with mesh awnings.
- » With vertical walls, creating 25% more inner volume.
- » Enhanced ventilation thanks to large windows and gable ventilation openings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Can be used for storage, hospital, dispensary, school, office , ...

MAIN MATERIALS

OUTER TENT LINER	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
SHADE COVER	Woven PE 175 gsm - water, rot and UV proof - FR CPAI-84 Section 6
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 Section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords Metal spring or elastic shock absorbers Red metal guy runner

UNICEF STANDARD
CUSTOMER REFERENCE


HPT - S5088072

XPERT TENT 72 SQM

DIMENSIONS

LENGTH x WIDTH OUTER TENT	1200 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	330 cm
DOORS (H x W)	(H x W) 1 per gable 200 x 190 cm
WINDOWS	6 per side 135 x 135 cm

GRAPHIC REFERENCE



PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected, not sensitive to fungi/mould
RESISTANCE WIND	Min. 100 km/h with shade net
SNOW LOAD	Min. 300 N/m ² with wire cable with tensioner
COLOR	Tent liner: white Groundsheet: grey

XPERT TENT 72 SQM

TENT FEATURES

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling.
DOOR	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	2 windows on each side.
SHADE COVER	With anti-water pockets and integrated fuse systems for enhanced wind resistance and better roof load.
VENTILATION	Triangular gable top ventilation opening and side wall ventilation above each window.
AIR INLET	Ø 35 cm at left bottom side of each gable (inside view).
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap.
GROUNDSHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.
PEGS	4 T-Peg 50 cm, 14 T-Peg 40 cm, 18 Rebar Peg 60 cm, 4 earth anchors.

PACKING

	Packed into 4 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags.
PACKING UNIT (P.U.)	Box 1: 225 x 87 x 28 cm - 116 kg (2 carry bags) Box 2: 225 x 87 x 26 cm - 139 kg (3 carry bags) Box 3: 225 x 87 x 22 cm - 139 kg (3 carry bags) Box 4: 225 x 87 x 27 cm - 141 kg (3 carry bags)
CONTENT P.U.	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
P.U. MEASUREMENTS	DIMENSIONS: 225 x 87 x 112 cm (incl. blocks) WEIGHT: ± 535 kg VOLUME: 2,19 m ³ (+- 1%)
LOADING	PER 20 FT DC 12 pcs palletized PER 40 FT DC 26 pcs palletized PER 40 FT HC 26 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

ADD-ONS

Connectability options (gable / lateral / cross connector)	Sanitary solutions: toilet cabin / shower cabin
Partition set	Lighting kits
Ceiling net	Hard flooring
Inner and winter liner: breathable FR fabric / breathable ` quilted FR fabric.	A/C and heating solutions
Cabins: individual cabin / isolation cabins / negative pressure cabins	

XPERT TENT 72 SQM

VISUAL REFERENCES

