

RECYCLED HIGH THERMAL FLEECE BLANKET

BLANKETS



ICRC/IFRC STANDARD

CUSTOMER REFERENCE

HSHEBLANPHT1

05786

DESCRIPTION

- » Knitted blanket dry raised on both sides
- » 2 fold fleece layers + 1 polyfill layer in **100% recycled polyester**
- » Min. 500 gsm - max. 1000 gsm

MAIN MATERIALS

MATERIAL	100% recycled polyester on dry weight as per ISO 1833 + recycled polyfil lining
TENSILE STRENGTH	Min. 250 N warp and weft as per ISO 13934-1
TENSILE STRENGTH LOSS	Less than 5% after washing as per ISO 6330 & ISO 13934-1
THICKNESS	Min 9,5mm as per ISO 5084 (1KPA on 2000 mm ²)
SHRINKAGE	Less than 5% after washing as per ISO 6330
WEIGHT LOSS	Less than 5% after washing as per ISO 6330
TOG	Min. 0,4 RCT (= 4 TOG)
RESISTANCE TO AIRFLOW	Less than 1000 L/m ² /s as per ISO 9237 under 100 Pa pressure drop
FINISH	Whipped seam of min. 10 stitches per 10 cm
ORGANOLEPTIC TEST	No bad smell, not irritating, no dust, PH between 4 and 9, fit for human use and free from harmful VOC
FLAME RESISTANCE	Flame proof as per ISO 12952-3&4
CIGARETTE RESISTANCE	Cigarette proof as per ISO 12952-1&2
COLOR	Grey shade blanket

DIMENSIONS

LENGTH x WIDTH	150 x 200 cm ± 1%
WEIGHT	Min. 500 g - max. 1000 gsm

RECYCLED HIGH THERMAL FLEECE BLANKET

BLANKETS



PACKING - 15 PCS PER BALE

PACKING UNIT (P.U.)	Waterlight bale
QTY P.U.	15 pcs per bale
P.U. MEASUREMENTS (15 pcs per bale)	DIMENSIONS: 80 x 57 x 51 cm WEIGHT: 25 kg VOLUME: 0,23 m ³
QTY PALLET	4 to 8 bales per CRI pallet
PALLET MEASUREMENTS	DIMENSIONS: 115 x 75 x 230 cm WEIGHT: 236 kg VOLUME: 2 m ³
LOADING (15 pcs per bale)	PER 20 FT DC 1850 pcs unpalletized 1680 pcs palletized PER 40 FT DC 3700 pcs unpalletized 3600 pcs palletized PER 40 FT HC 4350 pcs unpalletized 3600 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.
FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

Specifications & design may be altered without notice due to continuous product development.
LAST UPDATED 6/2023