# **BASE TENT 45 SQM**



RESISTANT















**ICRC/IFRC STANDARD CUSTOMER REFERENCE** HSHFTFNTM45

## **DESCRIPTION**

- » Multipurpose tent, can be used for storage, hospital, dispensary, school, office, ...
- » Tents can be connected one to another to make a longer structure
- » Various options available (inner tent, partitions sets,...)

### **MAIN MATERIALS**

**OUTER TENT LINER** Roof: 440 gsm polyester cotton - water, rot and UV proof

Wall: 320 gsm polyester cotton - water, rot and UV proof

MUD FLAP 550 gsm polyester with PVC coating on both sides - water, rot and UV proof **GROUND SHEET (OPTIONAL)** 

 $550~\mbox{gsm}$  polyester with PVC coating on both sides - water, rot and UV proof

FRAME Aluminium pipe Ø 42 x 2 mm with steel cross piecesGalvanized steel pipe Ø 30 x 1,5 mm

### **DIMENSIONS**

LENGTH x WIDTH OUTER TENT 600 x 750 cm FLOOR SURFACE 45 sqm CENTRAL HEIGHT 300 cm WALL HEIGHT 211 cm





## **BASE TENT 45 SQM**

#### PERFORMANCE AND CHARACTERISTICS

SHELF LIFE Min. 3 years

LIFE SPAN Min. 12 months exposure in all climates, with proper anchoring and maintenance

**TREATMENT** Fungi/mould resistant treated **SETUP** Easy setup (40 min | 5 persons) COLOR Tent liner: natural white

Groundsheet: grey

### **PACKING**

PACKING UNIT (P.U.) 2 PVC bundles joined together as a sandwich pack

CONTENT P.U. Tent, frame, accessories and hammer

QTY P.U.

DIMENSIONS: 230 x 95 x 35 cm

P.U. MEASUREMENTS WEIGHT: 208 kg

VOLUME: 0,765 m<sup>3</sup>

QTY PALLET

DIMENSIONS: 225 x 95 x 112,5 cm

PALLET MEASUREMENTS WEIGHT: 649 kg

VOLUME: 2,405 m<sup>3</sup>

PER 20 FT DC 36 pcs palletized LOADING PER 40 FT DC 72 pcs palletized

PER 40 FT HC 72 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALLDIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

### **ADD-ONS**

Connectability options (gable / lateral / cross connector)

Groundsheet

Partition set

Shade net

Inner liner

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 6/2023

